



## CC-HS2-L1-I

CC-HS2-L1-I

Camera lens behind by the special front cover  
 Ceiling mount spot light outlook with camera embedded  
 Built-in DNR (Digital Noise Reduction)  
 1/3" color CCD sensor for clear video output

### Specifications

Model Number		CC-HS2-L1-I
Scanning System	NTSC	525 lines 2:1 interlace
	PAL	625 lines 2:1 interlace
Scanning Frequency	NTSC	15,734Hz(H) , 60Hz(V)
	PAL	15,625Hz(H) , 50Hz(V)
Effective Pixels	NTSC	768(H) x 492(V)
	PAL	752(H) x 582(V)
Electronic Shutter	NTSC	1/60-100,000sec.
	PAL	1/50-100,000sec
Image Device	1/3" SONY Super HAD CCD	
Horizontal Resolution	560 TV lines Enhanced	
Sensitivity	0.2Lux, 0 Lux at IR on	
Signal to Noise	More than 52dB	
Gain Control	Auto + 18dB Max	
White Balance	Auto ATW 2500-9500°K	
Sense-UP times	Max 32 times	
DNR	Built-in DNR (Digital Noise Reduction)	
BLC	Auto	
Gamma Correction	0.45	
SYNC System	Internal	
Lens/Focus point	4.3mm (Optional 6mm)	
Video Output	1.0 Vp-p, 75 Ohm	
IR LED	12 units 940nm infrared LED	
IR Distance	15 meters (Subject to IR reflection conditions)	
IR Status	IR on: Under 10 Lux, by CDS auto control	
LED life	More than 10,000 Hours	
Protection Class	-	
Power Requirement (± 10%)	DC12V, 500mA	

Power Consumption (± 10%)	IR on: 180mA, IR off: 80mA
Operation Temp.	Operating: -10 ~ + 55°C , Storage: -30 ~ + 70°C , Humidity:0~95%RH
Dimensions ( mm )	90(R) x 48(H)
Weight ( N.W )	0.26kg